

## <u>DECLARATION of PERFORMANCE</u> <u>according to Annex III of the regulation (EU) Nr. 305/2011 (construction product regulation)</u> Nr. EJOT 4-008-170835-2019/2

**1.)** Unique identification code of the product-type:

EJOT Concrete screw JC2

**2.)** Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Type and lot number are displayed on the packaging

**3.)** Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Concrete screw of size 6, 8 and 10 for use in cracked and non-cracked concrete

**4.)** Name,registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

EJOT Baubefestigungen GmbH, In der Stockwiese 35, 57334 Bad Laasphe

**5.)** Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

**6.)** System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

- **7.)** In case of the declaration of performance concerning a construction product covered by a harmonized standard: Not relevant
- 8.) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Eurofins Expert Services, the notified body 0809, performed the system 1 requirements:

- Initial inspection of the manufacturing plant and factory production control
- Continuous surveillance, assessment and evaluation of factory production control and issue the certificate of conformity 0809-CPR-1261.
- **9.)** Declared performance:

| ESSENTIAL CHARACTERISTICS                   | DESIGN METHOD                | PERFORMANCE               | HARMONIZED<br>TECHNICAL<br>SPECIFICATION |
|---|------------------------------|---------------------------|--|
| CHARACTERISTIC RESISTANCE                   | EOTA TR 055, CEN/TS 1992-4-4 | ETA-17/0835, Annex C1     |  |
| FOR TENSION                                 | EOTA TR 020                  | ETA-17/0835, Annex C3     |  |
| CHARACTERISTIC RESISTANCE                   | EOTA TR 055, CEN/TS 1992-4-4 | ETA-17/0835, Annex C2     |  |
| FOR SHEAR                                   | EOTA TR 020                  | ETA-17/0835, Annex C4     | EAD 220222 00 0004                       |
| MINIMUM SPACING AND                         | EOTA TR 055, CEN/TS 1992-4-4 | ETA-17/0835, Annex B2     | EAD 330232-00-0601                       |
| MINIMUM EDGE DISTANCE                       | EOTA TR 020                  | ETA-17/0835, Annex C3, C4 |  |
| DISPLACEMENT FOR SERVICEABILITY LIMIT STATE | EOTA TR 055, CEN/TS 1992-4-4 | ETA-17/0835, Annex C5     |  |

**10.)** The performance of the product according to paragraph Nr 1 and 2 corresponds to the declared performance in Nr. 9. Responsible for creating this product performance is only the manufacturer according to Nr. 4.

Signed for and in the name of the manufacturer:

Dr. Jens Weber / Vice President

(Name and function)

Bad Laasphe 06.02.2019 (Place and date of issue)

(Signature)